



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ :G11B 27/32, H04N 5/775, G11B 27/10,
19/02, H04N 5/92, 9/82, G11B 27/34 //
H04N 5/85, G11B 7/00

A1

(11) International Publication Number:

WO 00/60597

(43) International Publication Date:

12 October 2000 (12.10.00)

(21) International Application Number: PCT/JP00/01995

(22) International Filing Date: 30 March 2000 (30.03.00)

(30) Priority Data:

11/96516	2 April 1999 (02.04.99)	JP
2000/57116	2 March 2000 (02.03.00)	JP

(71) Applicant: MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8501 (JP).

(72) Inventors: MURASE, Kaoru; 2-8-29-105, Meyasukita, Ikaruga-cho, Ikoma-gun, Nara 636-0133 (JP). OKADA, Tomoyuki; 6-6-101, Myokenzaka, Katano-shi, Osaka 576-0021 (JP). TSUGA, Kazuhiro; 9-33, Tsutsujigaoka, Hanayashiki, Takarazuka-shi, Hyogo 665-0803 (JP). SUGIMOTO, Noriko; 1-13-11, Nakayamadai, Takarazuka-shi, Hyogo 665-0876 (JP).

(74) Agents: AOYAMA, Tamotsu et al.; Aoyama & Partners, Imp Building, 3-7, Shiromi 1-chome, Chuo-ku, Osaka-shi, Osaka 540-0001 (JP).

(81) Designated States: CN, ID, KR, MX.


Published

*With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(54) Title: OPTICAL DISC, RECORDING DEVICE AND REPRODUCING DEVICE

(57) Abstract

Optical discs formatted to record plural audio streams of different content for reproduction with a single video stream can result in audio output of content unexpected by the user depending upon the audio stream configuration contained in the AV stream reproduced. This can confuse and cause the user to change the audio output after reproduction starts. To prevent this, information indicating the type of audio stream configuration contained in each AV stream on the optical disc is stored with each audio stream. This audio stream type information is presented to the user on the same screen from which an AV program is selected for playback. The user can thus know before playback starts what audio stream channel is preselected for playback, and can change the audio channel as desired before playback starts.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

DESCRIPTION

OPTICAL DISC, RECORDING DEVICE
AND REPRODUCING DEVICE

5

Technical Field

The present invention relates to a readable and writable optical disc, and to a recording device and a reproducing device for the optical disc. More particularly, our invention relates to an optical disc for recording multimedia data including moving picture data, still image data, and audio data, and to a recording device and a reproducing device for this optical disc.

15 Background Art

Rewritable optical discs have for years had a maximum storage capacity of approximately 650 MB, but this has been changed by the development of phase change type DVD-RAM discs with a capacity of several gigabytes. Combined with the adoption of MPEG, and particularly MPEG-2, standards for encoding digital AV data, DVD-RAM is widely anticipated as a recording and reproducing medium with application in the AV industry as well as the computer industry. More specifically, DVD-RAM media are expected to replace magnetic tape as the storage medium

of choice for AV recordings.

A. DVD-RAM

Increases in the storage density of rewritable
5 optical disc media over the last few years has made it
possible to use such media for applications ranging from
storing computer data and recording audio data to recording
image data, including movies.

The signal recording surface of a conventional
10 optical disc is typically formatted with lands and grooves,
one of which is used as a guide groove for signal recording
and reproducing. The data signal is then recorded using
only the land or the groove. With the advent of the land and
groove recording method, however, it became possible to
15 record signals to both the land and groove. This
development approximately doubled the storage capacity of
the disc.

Further development of a zone CLV (constant
linear velocity) method simplified and made it easy to
20 implement a CLV recording and reproducing technique, an
effective means of further increasing the recording density.

A major topic left for future development is how
to use such potentially high capacity optical disc media to
record AV data containing image data to achieve new
25 functions and performance far surpassing conventional AV

products.

With the introduction of high capacity rewritable optical disc media, optical discs are widely expected to replace conventional tape media for recording and reproducing AV content. The transition from tape to disc recording media is also expected to greatly affect both the performance and functions of AV recording and reproducing products.

One of the greatest benefits of a transition to disc is a significant improvement in random access performance. While random access to tape content is possible, it generally takes on the order of minutes to rewind a full tape. This is several orders slower than the typical seek time of optical disc media, which is on the order of at most several ten milliseconds. Tape is therefore considered, for practical purposes, not to be a random access medium.

The random access capability of optical disc media has also made possible distributed, that is, noncontiguous, recording of AV data, which is not possible with conventional tape.

Fig. 34 is a block diagram of the drive device of a DVD recorder. As shown in Fig. 34, this DVD recorder comprises an optical pickup 11 for reading data from the disc 10, an ECC (error correction code) processor 12, track

buffer 13, switch 14 for changing track buffer input/output, encoder 15, and decoder 16. An enlarged view of the disc 17 format is also shown.

As indicated by the disc 17 format, the smallest
5 unit used for recording data to a DVD-RAM disc is the sector, which is 2 KB. Sixteen sectors are combined as one ECC block, to which the ECC processor 12 applies error correction coding.

The track buffer 13 is used for recording AV data
10 at a variable bit rate in order to record AV data to a DVD-RAM disc more efficiently. While the read/write rate (V_a) to a DVD-RAM disc is fixed, the bit rate (V_b) of the AV data is variable, based on the complexity of the AV data content (e.g., images if the AV data is video). The track buffer 13 is
15 used to absorb this bit rate difference. This means that the track buffer 13 is unnecessary if the AV data bit rate is also fixed, as it is in the Video CD format.

This track buffer 13 can be even more effectively
used by dispersed placement of the AV data on the disc.
20 This is explained with reference to Fig. 35.

Fig. 35 (a) shows the disc address space. If the
AV data is recorded divided between contiguous area A1
between addresses a_1 and a_2 , and contiguous area A2
between a_3 and a_4 as shown in Fig. 35 (a), the AV data can
25 be continuously reproduced from these non-contiguous

areas A1 and A2 by supplying data accumulated in the track buffer 13 to the decoder while the optical head seeks from a2 to a3. This is shown in Fig. 35 (b).

Once reading AV data starts from a1 at time t1, it is both input to the track buffer 13 and output from the track buffer 13 with data accumulating in the track buffer at the rate $(V_a - V_b)$, that is, the difference between the input rate V_a to the track buffer and the output rate V_b from the track buffer. This continues to address a2 at time t2. Assuming that the data volume accumulated to the track buffer at this time is $B(t_2)$, data supply to the decoder can continue until the data $B(t_2)$ accumulated to the track buffer is depleted at time t3 at which reading resumes from address a3.

In other words, if it is assured that a certain volume of data ($[a1, a2]$) is read before a seek operation is performed, AV data can be continuously supplied to the decoder while the seek is in progress.

It should be noted that this example considers reading, that is, reproducing, data from DVD-RAM, but the same concept applies for writing or recording data to DVD-RAM.

It will thus be obvious that insofar as a specified amount of data is recorded continuously to DVD-RAM disc, continuous reproduction and recording is possible even if

the AV data is noncontiguously recorded to the disc.

B. MPEG

A common AV data format is described next
5 below.

As noted above, AV data is recorded to DVD-RAM media using the MPEG international standard, also known as ISO/IEC 13818.

Even though DVD-RAM discs have a large, plural
10 gigabyte, capacity, this is still not sufficient for recording uncompressed digital AV data of any duration. A way to compress and record AV data is therefore necessary. This need was addressed by worldwide adoption of the MPEG (ISO/IEC 13818) standard for AV data compression. MPEG
15 decoders (compression/decompression ICs) have also been realized with advances in IC devices. This has enabled the DVD recorder to handle MPEG compression and decompression internally.

MPEG signal processing is able to achieve high
20 efficiency data compression chiefly as a result of the following two features.

First is that compression using a time correlation characteristic between frames (known as pictures in MPEG) is used in conjunction with conventional compression using
25 a spatial frequency characteristic for moving picture data

compression. Each video sequence of an MPEG video signal stream is divided into one or more groups of pictures, each group of pictures comprising one or more pictures of three different types: I-pictures (intraframe coded pictures),
5 P-pictures (predictive-coded pictures, that is, intracoded with reference to a preceding picture), and B-pictures (bidirectionally predictive-coded pictures, that is, intraframe coded with reference to preceding and following pictures).

10 Fig. 36 shows the relationship between I, P, and B pictures. As shown in Fig. 36, P-pictures refer to temporally preceding I- or P-pictures in the sequence, while B-pictures refer to the first preceding and following I- or P-pictures. It should also be noted that because B-pictures
15 reference an upcoming I- or P-picture, the display order of the pictures may not match the coding order of the pictures in the compressed data bitstream.

The second feature of MPEG coding is that code size is dynamically allocated by picture unit according to
20 the complexity of the image. An MPEG decoder has an input buffer, and by accumulating data in this decoder buffer a large amount of code can be allocated to complex images that are difficult to compress.

Three types of audio coding are used for the
25 audio portion of a DVD-RAM recording: MPEG audio with

data compression, Dolby Digital^(R) (also known as AC-3), and noncompressive linear pulse code modulation (LPCM). Both Dolby Digital^(R) and LPCM are fixed bit rate coding methods, but MPEG audio coding can select from several compression rates on an audio frame basis, although audio compression is not as high as video stream compression.

The resulting compressed video and audio streams are multiplexed to a single stream using a method known as the MPEG system. Fig. 37 shows the organization of an MPEG system stream. As shown in Fig. 37, each 2 KB sector comprises a pack header 41, packet header 42, and payload 43. The MPEG system thus has a hierarchical structure comprising packs and packets. Each packet comprises a packet header 42 and payload 43. AV data is segmented from the beginning into blocks of an appropriate size for storage to the payload 43.

The packet header 42 records information referring to the AV data stored in the associated payload 43. More specifically, the packet header 42 contains a stream ID for identifying the data stored in the associated packet, and a decoding time stamp (DTS) and presentation time stamp (PTS) identifying the decoding time and presentation time of the data contained in the payload in 90 kHz precision. If the decoding and presentation are simultaneous, as in the case of audio data, the DTS can be

omitted.

A pack is a unit of plural packets. In DVD-RAM, however, there is one pack for each packet, and each pack therefore comprises a pack header 41 and packet
5 (containing a packet header 42 and payload 43).

The pack header contains a system clock reference (SCR) expressing with 27 MHz precision the time at which the data contained in this pack is input to the decoder buffer.

10 An MPEG system stream thus comprised is recorded one pack to a sector (= 2048 bytes) on DVD-RAM.

A decoder for decoding the above-noted MPEG system stream is described next below. Fig. 38 is a block diagram of an exemplary decoder model (P_STD) of an
15 MPEG system stream decoder. Shown in Fig. 38 are the system time clock (STC) 51, that is, the internal reference clock for decoder operation; a demultiplexer 52 for decoding (demultiplexing) the system stream; video decoder input buffer (video buffer) 53; video decoder 54; re-ordering
20 buffer 55 for temporarily storing I and P pictures to absorb the difference in the coding (data) sequence and presentation sequence that occurs between B pictures and I and P pictures; a switch 56 for adjusting the output order of the I, P, and B pictures buffered to the re-ordering buffer
25 55; an audio decoder input buffer (audio buffer) 57; and

audio decoder 58.

This MPEG system decoder processes the above-noted MPEG system stream as follows:

When the time indicated by the STC 51 and the
5 SCR written to the pack header match, the pack is input to
the demultiplexer 52. The demultiplexer 52 then interprets
the stream ID in the packet header, and passes the audio
stream and video stream contained in the payload data to
the appropriate decoder buffers. The PTS and DTS are also
10 read from the packet header.

When the times indicated by the STC 51 and DTS
match, the video decoder 54 reads and decodes the picture
data from the video buffer 53. I and P pictures are stored to
the re-ordering buffer 55 while B pictures are presented
15 directly to screen. If the picture being decoded by the video
decoder 54 is an I or P picture, the switch 56 switches to
the re-ordering buffer 55 to output the previous I or P
picture from the re-ordering buffer 55; if a B picture is
decoded, the switch 56 switches to the video decoder 54.

20 Similarly to the video decoder 54, the audio
decoder 58 reads and decodes one audio frame of data
from the audio buffer 57 when the PTS matches the STC 51
(a DTS is not recorded for audio data).

An exemplary method of multiplexing an MPEG
25 system stream is described next with reference to Fig. 39.

Note that a sequence of video frames is shown in Fig. 39 (a), the change in data storage to the video buffer is shown in Fig. 39 (b), a typical MPEG system stream is shown in Fig. 39 (c), and an audio signal is shown in Fig. 39 (d).

5 Each of Figs. 39 (a) to (d) are shown on a common time base (horizontal axis). The vertical axis in Fig. 39 (b) indicates the amount of data stored to the video buffer. The bold line in this graph thus indicates the change over time in the buffered video data volume. The slope of this line is indicative of the video bit rate, and shows that data is input to the video buffer at a constant rate. The decrease in buffered data at regular intervals indicates the progression of data decoding. The intersection of the dotted line extension of the graphed line with the time base (horizontal axis) indicates the time at which video frame transfer to the video buffer begins.

10

15

MPEG encoding is described next using by way of example coding a complex image A in the video data stream. As shown in Fig. 39 (b), image A requires a large coding block, and data transfer to the video buffer must therefore begin from a time t_1 before the image A decoding time. Note that the time from data input start time t_1 to decoding is referred to as vbv_delay below. AV data is thus multiplexed to the position (time) of the shaded video pack.

20

25 Unlike video data, audio data does not require

dynamic coding size control. It is therefore not necessary for audio data transfer to start at a similarly advanced time before decoding starts, and audio data is thus typically multiplexed only slightly before decoding starts. Video data is thus multiplexed to the MPEG system stream before the audio data.

It should be further noted that data can be accumulated to the buffer for a limited time in the MPEG system. More specifically, the MPEG system standard requires all data other than still image data be output to the decoder from the buffer within one second of being stored to the buffer. This means that there is at most a one second offset between video data and audio data multiplexing (or more precisely, the time required for video frame reordering).

It will also be obvious that while the MPEG system stream is described above with video data preceding the audio, the audio can theoretically precede the video. This type of stream can be purposely generated by using for the video data simple images to which a high compression rate can be applied, and transferring the audio data earlier than required. Even in this case, however, the audio can precede the video by at most one second due to the restrictions imposed by the MPEG standard.

Audio stream format and reproduction

The format of the audio stream and a method for audio stream reproduction are described next below.

As described above, data is recorded and reproduced from a linear recording area in sequential access media such as magnetic tape. A typical method for recording an audio stream to a plurality of tracks on a single tape is described next below with reference to Fig. 41. In this example a maximum of two audio streams, shown as audio stream 1 and audio stream 2, can be recorded for a single video stream. In this example audio stream 1 is a single audio channel, generally known as a monaural audio channel, and audio stream 2 comprises two audio channels, such as a stereo audio signal or two monaural streams enabling a bilingual recording. It is also possible to record only one of these two audio streams (audio stream 1 or audio stream 2) or to record no audio stream. However, reducing the amount of audio recorded cannot be used as a means for increasing the video storage capacity of the tape. In other words, the audio stream recording area, i.e., the audio track space, is reserved exclusively for audio content and cannot be used for any other application even when no audio stream is actually recorded. The user can also select which of the two audio streams and channels to play, and the audio stream or channel selected by the user is

reproduced simultaneously with the video.

DVD-RAM and other disc media, however, allow for more flexible audio stream recording and reproduction. The number of audio streams and channels recorded simultaneously with a video stream can be varied for the plurality of audio streams recorded to a disc.

Fig. 42 shows some of the ways in which the audio stream content can be varied with the video stream in a disc media. For example, AV stream 1 in Fig. 42 (a) comprises one audio stream for the video stream, and the audio stream in this case has only one channel.

AV stream 2 in Fig. 42 (b) similarly comprises one audio stream for the same video stream, but the audio stream in this case comprises two channels, i.e., main and sub audio channels. In this case the audio stream contains two selectively reproducible audio channels, a first audio channel containing the main audio (such as a first language), and a second audio channel containing the auxiliary audio data of the sub channel (such as a second language).

AV stream 3 in Fig. 42 (c) comprises two audio streams for the video stream. In this case audio stream 1 is a single monaural channel while audio stream 2 contains two channels. The beginning of this audio stream 2 is recorded in stereo and then switches to dual monaural

audio content. More specifically, audio stream 2 in this example comprises at least two of the following three audio content areas: a second (stereo) area containing first and second simultaneously reproduced audio channel data; a first (dual monaural) area containing first and second audio channels of which only one is selected and reproduced; and a third (monaural) area containing only one audio channel.

It will also be obvious that audio content is not limited to these stereo, dual monaural, and monaural types, and this audio stream 2 is simply illustrative of an audio stream containing a mix of different audio types. In the example shown in Fig. 42 (c), audio stream 2 contains a stereo and a dual monaural area. Exemplary stereo content might be the commercials in a television broadcast while the dual monaural content contains separate audio streams of a bilingual broadcast in, for example, Japanese and English.

As noted above the relationship between video and audio streams on DVD-RAM and other disc media is flexible with the audio stream configuration being easily adapted according to the application and objective of the plural AV streams recorded to any same disc. It should be noted here that the AV stream configuration shown in Fig. 42 mimics a tape track configuration simply for ease of illustration and understanding. The actual AV stream

configuration is a multiplexed bit stream of video stream data and one or more audio streams as shown in the MPEG system stream in Fig. 39 (c).

5 Disclosure Of Invention

The object of the present invention is to provide a DVD recorder that solves the following problems hindering obtaining maximum performance from DVD-RAM media, a high capacity rewritable storage medium widely
10 anticipated as the next generation in AV recording media.

As described with reference to Fig. 42 (a) to (c), one or a plurality of audio streams can be freely recorded to DVD-RAM media with each audio stream containing a variable number of channels. The user can tell the number
15 of audio streams and the channel configuration thereof by reproducing the AV stream to which this audio stream is recorded, but cannot know this information by simply loading the disc into the DVD-RAM disc player.

An object of the present invention is therefore to
20 provide a disc format whereby the user can know the audio stream configuration of a recorded AV stream before actually reproducing the AV stream.

Our invention further makes it possible for the user to know the audio stream configuration for each of one
25 or a plurality of AV streams recorded to a DVD-RAM disc

when the disc is loaded into a DVD-RAM disc player.

The greatest problem confronted by enabling a DVD recorder to record a flexible correlation between video streams and audio streams so that different audio stream configurations can be achieved for each AV stream on the disc is how to manage the data internally and how to present the data to the user.

The internal data management technique must be able to manage a variety of audio stream configurations while also achieving recording, reproducing, and editing functions without introducing incompatibilities and content mismatches.

A diverse range of audio stream configurations enables finite recording space (capacity) to be used effectively, and enables recording various AV streams according to particular user objectives, but at the same time can introduce confusion. In other words, when a user wants to play a particular AV stream, the user cannot select the appropriate audio stream and audio channel(s) if the user does not know what audio stream configuration was recorded for the desired AV stream. For example, if both Japanese and English audio streams are recorded and both are selectable so that the user can listen in either language, the AV stream could be reproduced in the language not desired by the user as a result of how the disc player is set

up. Depending upon the circumstances it is also possible for the user to manually reselect the desired audio stream when the user realizes that the undesired audio stream is being reproduced.

5 There is therefore a need for a method of correctly selecting the desired audio stream and audio channel at the same time the desired AV stream is selected for reproduction.

 It is therefore an object of our invention to
10 provide a rewritable disc, such as a DVD-RAM disc, formatted such that information about the audio stream and audio channel configuration can be appropriately presented to the user using management information recorded to the disc when a plurality of audio stream configurations is
15 recorded for one video stream, and an audio stream to be reproduced can be automatically selected according to selection information defined by the user.

 To achieve the above object, our invention relates to an optical disc for storing an AV stream
20 containing a video stream and at least one audio stream, and management information for managing the AV stream. More particularly, our invention provides such an optical disc in which the audio stream recorded to the optical disc comprises an audio channel area containing first and
25 second audio channels, one of which is selectively

reproduced. In addition, the management information stores preference information indicative of whether the first audio channel data or second audio channel data is preferentially reproduced when reproducing the audio channel area.

5 Further preferably, the audio stream contains at least two of the following areas: a first area containing first audio channel data and second audio channel data, one of which is selectively reproduced; a second area containing simultaneously reproduced first audio channel data and
10 second audio channel data; and a third area containing data for one audio channel. In this case, the management information additionally contains application information indicating that two or more different audio stream areas are contained in one audio stream.

15 Our invention further provides a recording device for recording to an optical disc an AV stream containing a video stream and at least one audio stream, and management information for managing the AV stream. This recording device has an encoder (7804) for encoding an
20 audio stream having an area containing first audio channel data and second audio channel data, one of which is selectively reproduced; a controller (7802) for generating management information containing preference information indicating whether the first audio channel data or second
25 audio channel data is to be preferentially reproduced when

the audio channel area is reproduced; and drive means (7807, 7808) for recording the encoded audio stream and management information to a data area of the optical disc.

Further preferably, the encoder further encodes an audio stream containing at least two of the following areas: a first area containing first audio channel data and second audio channel data, one of which is selectively reproduced; a second area containing simultaneously reproduced first audio channel data and second audio channel data; and a third area containing data for one audio channel. The controller in this case generates management information containing application information indicating that two or more different audio stream areas are contained in one audio stream.

Our invention also provides a playback device for reproducing an AV stream containing a video stream and at least one audio stream, and management information for managing the AV stream, from an optical disc. This playback device has reading means (7807, 7808) for reading management information from a data area of the optical disc; extraction means (7802, Step #26) for extracting preference information contained in the management information; and a decoder (7806) for selecting and decoding audio channel data indicated by the preference information. The preference information

indicates whether the first audio channel data or second audio channel data is to be preferentially reproduced when reproducing the area containing the first audio channel data or second audio channel data of which one is selectively reproduced.

Further preferably, this playback device additionally has an output means (7805) for displaying the preferred audio channel determined from the preference information.

Yet further preferably, the extraction means of this playback device also extracts application information indicating two or more areas of different type are mixed in a single audio stream; and the output means displays information indicating that a mixture of audio types is recorded to the AV stream.

Brief Description Of Drawings

These and other objects and features of the present invention will be readily understood from the following detailed description taken in conjunction with preferred embodiments thereof with reference to the accompanying drawings, in which like parts are designated by like reference numerals and in which:

Fig. 1 shows the logical structure of a disc according to a preferred embodiment of the present

invention;

Fig. 2 shows the internal structure of an AV file
for movies;

Fig. 3 shows the internal structure of an AV file
5 for still images;

Fig. 4 shows the relationship between AV data
and management information;

Fig. 5 shows the structure of the RTR_VMG
block;

10 Fig. 6 shows the structure of the RTR_VMGI
block;

Fig. 7 shows the VERN and TM_ZONE format;

Fig. 8 shows the structure of the PL_SRP block;

Fig. 9 shows the PL_TY and PL_CREATE format;

15 Fig. 10 shows the PTM format;

Fig. 11 shows the S_VOB_ENTN format;

Fig. 12 shows the structure of the M_AVFIT
block;

Fig. 13 shows the V_ATR and A_ATR format;

20 Fig. 14 shows the SP_ATR and SP_PLT format for
movies;

Fig. 15 shows the structure of the M_AVFI block;

Fig. 16 shows the structure of the M_VOBI block;

Fig. 17 shows the VOB_TY format;

25 Fig. 18 shows the structure of the TMAPI block;

Fig. 19 shows the VOBU_ENT format;

Fig. 20 shows the structure of the S_AVFIT block;

Fig. 21 shows the V_ATR and OA_ATRS_AA_STI format;

5 Fig. 22 shows the SP_ATR and SP_PLT format for still images;

Fig. 23 shows the structure of the S_AVFI block;

Fig. 24 shows the structure of the S_VOB_ENT block;

10 Fig. 25 shows the S_VOB_ENT_TY format;

Fig. 26 shows the structure of the UD_PGCIT block;

Fig. 27 shows the structure of the TXTDT_MG block;

15 Fig. 28 shows the structure of the PGCI block;

Fig. 29 shows the PG_TY format;

Fig. 30 shows the structure of the CI block;

Fig. 31 shows the C_TY format;

Fig. 32 shows the structure of the C_EPI block;

20 Fig. 33 shows the EP_TY1 format;

Fig. 34 is a block diagram of a DVD recorder drive;

25 Fig. 35 (a) shows the volume address space of a disc, and (b) shows the change in data accumulation in the track buffer;

Fig. 36 shows the correlation between picture types in an MPEG video system stream;

Fig. 37 shows the structure of an MPEG system stream;

5 Fig. 38 is a block diagram of an MPEG system decoder (P_STD);

Fig. 39 (a) shows video data, (b) shows the change in data accumulation in the video buffer, (c) shows the MPEG system stream, and (d) shows the audio data;

10 Fig. 40 is a block diagram of a DVD recorder;

Fig. 41 is used to describe the audio stream configuration in a conventional AV stream;

Figs. 42(a), 42(b), 42(c) are used to describe audio stream configurations in an exemplary AV stream;

15 Fig. 43 shows the relationship between management information stored to disc and a first exemplary audio stream configuration;

Fig. 44 shows the relationship between management information stored to disc and a second
20 exemplary audio stream configuration;

Fig. 45 shows the relationship between management information stored to disc and a third exemplary audio stream configuration;

Fig. 46 is used to describe the management
25 information structure written to optical disc;

Fig. 47 is a flow chart of an operation for recording audio data management information to optical disc;

5 Fig. 48 is a flow chart of an operation for presenting a program list indicating the content of a disc inserted to the disc player;

Fig. 49 is a flow chart of an operation for reproducing a program recorded to a disc inserted to the disc player; and

10 Fig. 50 shows an exemplary program list generated from a disc inserted to the disc player and presented for the user.

Best Mode for Carrying Out the Invention

15 A DVD recorder and DVD-RAM disc are described below as a preferred embodiment of the present invention with reference to the accompanying figures.

Logical structure of DVD-RAM

20 The logical structure of a DVD-RAM disc is described first below with reference to Fig. 1. Fig. 1 shows the physical sector address area of the disc, and the structure whereby data is recorded to the disc as part of a file system.

25 The physical sector address area of the disc starts with a lead-in area to which a reference signal for

servo stabilization, and an ID signal for differentiating DVD-RAM media from other media, are recorded. The user data area follows the lead-in area. Logically valid data is recorded to the user data area. A lead-out area ends the physical sector address area; a reference signal is also recorded here.

File system management information, called volume information, is recorded at the beginning of the user data area. The file system is not directly related to the present invention, and description thereof is thus omitted below. It should be noted, however, that by using a file system, data recorded to the disc can be managed as files and a directory to the files as shown in Fig. 1.

All data handled by the DVD recorder is filed under the DVD_RTR directory directly below the root directory as shown in Fig. 1.

Files handled by a DVD recorder can be grouped into two broad categories: a management information file (RTR.IFO file) and one or more AV files (RTR_MOV.VRO file, RTR_STO.VRO file).

AV files are recorded as an RTR_MOV.VRO file recording moving picture content (referred to as video below), or an RTR_STO.VRO file recording still image data and simultaneously recorded audio data.

Fig. 2 shows the file structure of an

RTR_MOV.VRO file recording video content. As shown in Fig. 2, MPEG program streams (M_VOB (Movie Video Object)) are arranged in recording sequence in the RTR_MOV.VRO file.

5 Each program stream (M_VOB) is built from a plurality of Video Object Units (VOBU), each with a video reproduction time of 0.4 sec. to 1.0 sec.

 Each VOBU comprises a number of video packs (V_PCK), audio packs (A_PCK), and subpicture packs
10 (SP_PCK); each pack is 2 KB.

 The video data in each VOBU further comprises one or more Group of Pictures (GOP). The GOP is the decoding unit for MPEG video, starts with an I-picture, and contains plural P- or B-pictures.

15 Fig. 3 shows the structure of an RTR_STO.VRO file for recording still images and audio data. As shown in Fig. 3, an RTR_STO.VRO file contains S_VOB (Still Picture Video Objects), the MPEG program stream for still images, arranged in recording sequence.

20 The greatest difference between an S_VOB and M_VOB is that an S_VOB records still image data instead of moving picture data, and the still image data (video part) is followed by the audio data (audio part) instead of multiplexing the video and audio.

25 An S_VOB also contains one VOBU, which

comprises a V_PCK, A_PCK, and SP_PCK.

AV data and management information

5 The relationship between M_VOB, S_VOB, and management information is described next below with reference to Fig. 4.

 As described above, there are two types of AV data, M_VOB and S_VOB. Management information M_VOBI for each M_VOB is stored for each M_VOB where the
10 M_VOBI records attributes of the corresponding M_VOB. Individually managing S_VOBS, however, would greatly increase the amount of management information. Management information S_VOGL is therefore used to manage a group S_VOG containing plural S_VOB units. This
15 S_VOGL records attributes for the corresponding S_VOB group.

 What is important to note here is that MPEG stream data does not have a linear correlation between time and data size. As noted above, the MPEG system stream is
20 compressed using temporal correlation characteristics and variable length coding techniques (including variable bit rate coding) in order to achieve high compression efficiency. As a result there is not necessarily a direct correlation between time and data size (address).

25 Therefore, an M_VOBI also contains a filter

(TMAP) for converting time and address information, and an S_VOGL also contains a filter (S_VOB Entries) for converting a still image number in an S_VOG group and address.

5 Management information for the reproduction sequence is described next below.

 The reproduction sequence is defined as a program chain (PGC) or sequence of cells describing all or part of a range of M_VOB or S_VOG blocks.

10 The reproduction sequence can be either of two types: an original PGC referring to all AV data on the disc, or a user-defined PGC defining a user-selected reproduction sequence of AV data on the disc. Note that a plurality of user-defined PGC can be recorded.

15 The original PGC is also called a Program Set having a Program layer logically bundling a plurality of cells.

 A user-defined PGC is also called a Play List. Unlike an original PGC, a Play List does not have a
20 Program layer.

Management information file

 The content of the management information file RTR.IFO is described next below with reference to Fig. 5 to
25 Fig. 33.

RTR_VMG (Fig. 5)

The VR_MANGR.IFO file contains real-time recording video management information RTR_VMG.

RTR_VMG comprises seven tables: RTR_VMGI, M_AVFIT,
5 S_AVFIT, ORG_PGCI, UD_PGCIT, TXTDT_MG, and MNFIT.

These seven tables are described in detail next below.

RTR_VMGI (Fig. 6)

Real-time recording video management
10 information RTR_VMGI includes video management information table VMGI_MAT and play list search pointer table PL_SRPT.

VMGI_MAT (Fig. 6)

The video management information management
15 table VMGI_MAT stores the following information relating to the entire disc. The reproducing device and recording device, referred to as simply disc player and recorder, respectively, below, first read this VMGI_MAT to detect the overall structure of the disc.

20 VMG_ID (video management identifier)

Stores the identifier DVD_RTR_VMG0 identifying the disc as storing video recording data.

RTR_VMG_EA (RTR_VMG end address)

Stores the RTR_VMG end address.

25 VMGI_EA (VMGI end address)

Stores the VMGI end address.

VERN (version number)

Records the version number of the recording format of the stored video recording data according to the format shown in Fig. 7.

TM_ZONE (time zone)

Records the time zone used for all time information recorded to the disc. As shown in Fig. 7, the TM_ZONE stores a time zone stamp TZ_TY indicating whether time information is based on Greenwich Mean Time or a regional time standard (such as Eastern Standard Time (EST) or Japan Standard Time (JST)), and a time zone offset TZ_OFFSET recording the time difference to Greenwich Mean Time.

STILL_TM (still time)

Stores the still time used for presenting still images without sound.

CHRS (character set code for primary text display)

Defines the character set code to use for primary text displays (described below).

M_AVFIT_SA (M_AVFIT start address)

Stores the start address of the movie AV file information table M_AVFIT. This start address is used in the seek operation for accessing the M_AVFIT table.

S_AVFIT_SA (S_AVFIT start address)

Stores the start address of the still image AV file information table S_AVFIT. This start address is used in the seek operation for accessing the S_AVFIT table.

ORG_PGCI_SA (ORG_PGCI start address)

5 Stores the start address of the original PGC information. This start address is used in the seek operation for accessing the original PGC.

UD_PGCIT_SA (UD_PGCIT start address)

10 Stores the start address of the user-defined PGC information table. This start address is used in the seek operation for accessing the user-defined PGC information table.

TXTDT_MG_SA (TXTDT_MG start address)

15 Stores the start address of the text data management information TXTDT_MG. This start address is used in the seek operation for accessing the text data management information TXTDT_MG.

MNFIT_SA (MNFIT start address)

20 Stores the start address of the management file information table MNFIT. This address is used in the seek operation for accessing the MNFIT table.

PL_SRPT (play list search pointer table) (Fig. 8)

25 The play list search pointer table PL_SRPT records play list search pointer table information PL_SRPTI

and n play list search pointers PL_SRP.

PL_SRPTI (play list search pointer table information)

(Fig. 8)

5 The play list search pointer table information
PL_SRPTI records the following information for accessing a
play list search pointer PL_SRP.

PL_SRP_Ns (number of play list search pointers)

Stores the number of play list search pointers

10 PL_SRP.

PL_SRPT_EA (PL_SRPT end address)

	Stores the end address of this play list search
pointer	table PL_SRPT.

15 PL_SRP (play list search pointer) (Fig. 8)

Records the following information for accessing the actual play list data, that is, the user-defined PGC.

PL_TY (play list type)

Stores one of the following values for identifying
20 the play list type using the format shown in Fig. 9.

0000b: video only

0001b: still images only

0010b: both video and still images

0011b: audio only

PGCN (PGC number)

Stores the PGC number for the associated play list. The PGC number is the recording sequence of PGC information in the UD_PGCIT described below.

5 PL_CREATE_TM (play list creation date/time)

Stores the date and time the play list was created according to the format shown in Fig. 9.

PRM_TXTI (primary text information)

10 Stores text information indicative of play list content. For example, if the play list is a television program, PRM_TXTI could record the name of the show. PRM_TXTI includes an ASCII code field, and a field for the character code set defined by the above-noted CHRS.

IT_TXT_SRP (IT_TXT_SRP number)

15 If information indicative of the play list content is recorded as the optional IT_TXT block in addition to the above-noted primary text, the IT_TXT_SRP number is stored as a link to the IT_TXT recorded in TXTDT_MG. This IT_TXT_SRP number is the recording sequence in
20 TXTDT_MG, described below.

THM_PTRI (thumbnail pointer information)

Stores thumbnail image information for the play list.

25 THM_PTRI (Fig. 8)

THM_PTRI stores the following information indicating a thumbnail image location.

CN (cell number)

Stores the cell number containing the thumbnail
5 image. The cell number is the recording sequence of the cell information in the UD_PGCI for this play list.

THM_PT (thumbnail image pointer)

Stores the presentation time of the video frame
used as the thumbnail image according to the PTM
10 (presentation time) describing format as shown in Fig. 10 if the cell indicated by CN is a video cell. PTM is written according to the reference time of the time stamp written in the MPEG program stream.

Stores the still image VOB entry number of the
15 still image used as the thumbnail image according to the S_VOB_ENTN describing format as shown in Fig. 11 if the cell indicated by CN is a still image cell.

M_AVFIT (Fig. 12)

20 The movie AV file information table M_AVFIT stores management information for the movie AV file RTR_MOV.VRO, and comprises M_AVFITI, M_VOB_STI, and M_AVFI.

25 **M_AVFITI (movie AV file information table information)**

(Fig. 12)

Stores the following information for accessing

M_VOB_STI and M_AVFI.

M_AVFI_Ns (movie AV file information number)

5 Indicates the number of following AVFI
information fields. If 0, no AVFI is present; if 1, an AVFI is
present. AVFI presence corresponds to the presence of
movie AV file RTR_MOV.VRO.

M_VOB_STI_Ns (M_VOB_STI number)

10 Indicates the number of following M_VOB_STI
fields.

M_AVFIT_EA (M_AVFIT end address)

Stores the M_AVFIT end address.

15 M_VOB_STI (movie VOB stream information) (Fig. 12)

Stores the following as movie VOB stream
information.

V_ATR (video attributes)

20 Stores the following video attributes according to
the format as shown in Fig. 13.

Video compression mode

Stores one of the following values indicating the
video compression mode.

00b: MPEG_1

25 01b: MPEG_2

TV system

Stores one of the following values indicating the television system.

00b: 525/60 (NTSC)

5 01b: 625/50 (PAL)

Aspect ratio

Stores one of the following values indicating the aspect ratio.

00b: 4x3

10 01b: 16x9

line21_switch_1

Stores one of the following values indicating whether closed caption data for field 1 is contained in the video stream.

15 1b: recorded

0b: not recorded

line21_switch_2

Stores one of the following values indicating whether closed caption data for field 2 is contained in the video stream.

20

1b: recorded

0b: not recorded

Video resolution

Stores one of the following values indicating the video resolution.

25

000b: 720x480 (NTSC), 720x576 (PAL)

001b: 702x480 (NTSC), 702x576 (PAL)

010b: 352x480 (NTSC), 352x576 (PAL)

011b: 352x240 (NTSC), 352x288 (PAL)

5 100b: 544x480 (NTSC), 544x576 (PAL)

101b: 480x480 (NTSC), 480x576 (PAL)

AST_Ns (audio stream number)

Stores the number of audio streams recorded to the corresponding VOB.

10 SPST_Ns (still picture stream number)

Stores the number of still picture streams recorded to the corresponding VOB.

A_ATR0 (audio stream 0 attributes)

15 Stores the following attributes for the audio recorded to audio stream 0 using the format as shown in Fig. 13.

Audio coding mode

Stores one of the following values indicating the audio compression method.

20 000b: Dolby AC-3

001b: MPEG audio without an extension stream

010b: MPEG audio with an extension stream

011b: linear PCM

Preference flag

25 Stores one of the following values indicating user

preference information for the audio channel.

00b: not applicable

01b: audio channel 1

10b: audio channel 2

- 5 For example, if audio channel 1 is in Japanese, audio channel 2 is in English, and the user prefers to listen in English, this preference flag is set to 10b by the user.

Application Flag

- 10 Stores one of the following values indicating the audio application.

00b: not applicable

01b: plural audio channel configurations are mixed

10b: enhancement channel included

- 15 Note that a value of 01b indicating plural audio channel configurations are mixed means, for example, that two or more audio streams of monaural, stereo, or dual audio (such as in both Japanese and English) are recorded to the AV stream on separate time bases.

- 20 The enhancement channel is an enhanced audio channel for the visually impaired.

Quantization/DRC

Stores one of the following values for identifying whether dynamic range control (DRC) information is present.

00b: DRC not contained in MPEG stream

- 25 01b: DRC contained in MPEG stream

If LPCM is used, the following value is stored to identify the quantization level.

00b: 16 bit.

fs

5 The following value is stored to identify the sampling frequency.

00b: 48 kHz

Number of Audio channels

10 Stores one of the following values indicating the number of audio channels.

0000b: 1 channel (monaural)

0001b: 2 channel (stereo)

0010b: 3 channel

0011b: 4 channel

15 0100b: 5 channel

0101b: 6 channel

0110b: 7 channel

0111b: 8 channel

1001b: 2 channel (dual monaural)

20 Dual monaural refers, for example, to a bilingual recording with main (e.g., Japanese) and sub (e.g., English) channels, both of which are monaural.

Bitrate

25 Stores one of the following values indicating the bitrate.

0000 0001b: 64 kbps

0000 0010b: 89 kbps

0000 0011b: 96 kbps

0000 0100b: 112 kbps

5 0000 0101b: 128 kbps

0000 0110b: 160 kbps

0000 0111b: 192 kbps

0000 1000b: 224 kbps

0000 1001b: 256 kbps

10 0000 1010b: 320 kbps

0000 1011b: 384 kbps

0000 1100b: 448 kbps

0000 1101b: 768 kbps

0000 1110b: 1536 kbps

15 What is important here is that if the
corresponding audio stream is an MPEG audio stream with
an extension stream, only the bitrate of the base stream,
not including the extension stream, is recorded. This is
because compression using a VLC technique is used for the
20 extension stream, and the extension stream therefore
cannot be defined using a fixed bitrate as above.

A_ATR1 (audio stream 1 attributes)

Stores the following attributes of audio stream 1
using the format as shown in Fig. 13. Note that these
25 attributes are defined using the same fields used with

A_ATTR0 and described above, and further description is thus omitted here.

As shown in Fig. 43, if there are two audio streams (audio stream 1 and audio stream 2) for a single AV stream, A_ATTR0 is used for audio stream 1 management information, and A_ATTR1 is used for audio stream 2 management information. Because A_ATTR0 and A_ATTR1 are identical in structure, A_ATTR0 shown on the bottom in Fig. 13 is also applicable to A_ATTR1.

One possible application for two audio streams is to broadcast a baseball game, for example, with announcer commentary for one team broadcast in stereo on audio stream 1, and the announcer commentary for the other team broadcast in stereo on audio stream 2.

If there is only one audio stream, that is, audio stream 1 in this case as shown in Fig. 44, A_ATTR0 is used for the audio stream 1 management information while A_ATTR1 is left blank or as initialized.

Furthermore, if audio streams 1 and 2 are both recorded for a single AV stream, A_ATTR0 is used for audio stream 1 management information, and A_ATTR1 is used for audio stream 2 management information. By setting the preference flag to 10b in A_ATTR1 as shown in Fig. 45, audio channel 2, that is, the subchannel, can be designated the preferred channel and selected with priority to audio

channel 1. Furthermore, by setting the application flag to 01b it is known that a plurality of audio channels are mixed. By further setting the number of audio channels to 1001b, it is known that two channel (dual monaural) audio is the preferred mode. Which is the preferred or representative mode when there are plural modes can be detected by, for example, comparing the total time of each mode and selecting the mode with the longest time, or sending a code in the broadcast signal indicating a preselected preferred mode.

SP_ATR (subpicture attribute)

Records the subpicture attribute information shown below according to the format as shown in Fig. 14.

Application Flag

Stores one of the following values indicating the application type.

00b: not applicable

01b: caption

10b: animation

SP_PLT (subpicture color palette)

Records the subpicture color palette information using the format shown in Fig. 14.

M_AVFI (Fig. 15)

The movie AV file information M_AVFI comprises

the following information for accessing a movie VOB:
M_AVFI_GI, M_VOBI_SRP, and M_VOBI.

M_AVFI_GI (movie AV file general information) (Fig. 15).

5 Stores the movie VOB information search pointer count M_VOBI_SRP_Ns.

M_VOBI_SRP_Ns (movie VOB information search pointer number)

10 Records the number of movie VOB information search pointers M_VOBI_SRP.

M_VOBI_SRP (movie VOB information search pointer) (Fig. 15)

Stores address information for accessing each M_VOBI.

15 M_VOBI_SA (movie VOB information start address)

Stores the M_VOBI start address used for a seek operation accessing the corresponding VOB information.

M_VOBI (movie VOB information) (Fig. 16)

20 Stores the following movie VOB management information: M_VOB_GI, SMLI, AGAPI, TMAPI, and CP_MNGI.

M_VOB_GI (general information) (Fig. 16)

25 Records the following general information relating to a movie VOB.

VOB_TY (VOB type)

Stores VOB attributes according to the format as shown in Fig. 17.

TE

5 Stores one of the following values indicating the VOB status.

0b: normal

1b: temporarily or partially deleted

A0_STATUS

10 Stores one of the following values indicating the status of audio stream 0.

00b: original state

01b: overwritten

A1_STATUS

15 Stores one of the following values indicating the status of audio stream 1.

00b: original state

01b: overwritten

10b: dummy for additional audio content

20 11b: additional audio content added

APS

Stores one of the following values indicating the analog copy prevention control signal state.

00b: analog copy protection not enabled

25 01b: type 1

10b: type 2

11b: type 3

SML_FLG

5 Stores one of the following values indicating whether the VOB is to be seamlessly reproduced with the preceding VOB.

0b: seamless reproduction not possible

1b: seamless reproduction possible

A0_GAP_LOC

10 Stores one of the following values indicating the presence of an audio reproduction gap in audio stream 0, and identifying the VOBU to which the audio reproduction gap is multiplexed.

00b: no audio reproduction gap recorded

15 01b: audio reproduction gap multiplexed to first VOBU

10b: audio reproduction gap multiplexed to second VOBU

11b: audio reproduction gap multiplexed to third VOBU

A1_GAP_LOC

20 Stores one of the following values indicating the presence of an audio reproduction gap in audio stream 1, and identifying the VOBU to which the audio reproduction gap is multiplexed.

00b: no audio reproduction gap recorded

01b: audio reproduction gap multiplexed to first VOBU

25 10b: audio reproduction gap multiplexed to second VOBU

11b: audio reproduction gap multiplexed to third VOB

VOB_REC_TM (VOB recording date/time)

The date and time the VOB was recorded is
5 stored in the same format used for PL_CREATE_TM shown
in Fig. 9. What is important to note here is that this
indicates the date/time that the first video presentation
frame of the VOB was recorded. If the first video frame is
changed by editing or deletion, this VOB_REC_TM value
10 must be updated. It should be further noted that the
date/time of recording can be displayed synchronized to the
VOB presentation similarly to the way a date/time is
displayed on the viewfinder of a video camcorder by simply
adding the time elapsed in the VOB to the time stored as
15 VOB_REC_TM.

VOB_REC_TM_SUB (VOB recording date/time
difference information)

This field is used to absorb error in a
VOB_REC_TM field that has been updated because the first
20 video frame in the VOB was changed by VOB editing or
deletion. As shown in Fig. 9, VOB_REC_TM is only accurate
to the second. This means that if the video was edited or
deleted at the frame or field level (precision), the recording
time cannot be expressed with sufficient accuracy using
25 only VOB_REC_TM. This field is therefore used to adjust

for any difference.

M_VOB_STIN (M_VOB_STI number)

Stores the M_VOB_STI number corresponding to the VOB. This M_VOB_STI number is the recording sequence in the above-noted M_VOB_STI table.

VOB_V_S_PTM (VOB video start PTM)

Stores the VOB presentation start time based on the same reference time as the time stamp of the video stream.

VOB_V_E_PTM (VOB video end PTM)

Stores the VOB presentation end time based on the same reference time as the time stamp of the video stream. It should be noted that the time stamp of the stream indicates the presentation start time of the frame, but this VOB_V_E_PTM field records the presentation end time, that is, the sum of the start time plus the frame presentation period.

SMLI (seamless information) (Fig. 16)

SMLI stores the following information required for seamless reproduction with the preceding VOB. Note that this field is only recorded when the above-noted SML_FLG is 1b.

VOB_FIRST_SCR

Stores the SCR of the first pack in the VOB.

PREV_VOB_LAST_SCR

Stores the SCR of the last pack in the previous VOB.

AGAPI (audio gap information) (Fig. 16)

AGAPI records the following information required
5 for the decoder to process an audio reproduction gap. This field is only recorded when a value other than 00b is written to the above-noted A0_GAP_LOC or A1_GAP_LOC.

VOB_A_STP_PTM (VOB audio stop PTM)

Records the time of the audio reproduction gap,
10 that is, the time at which the decoder is to temporarily stop audio reproduction. This time is recorded using the same reference time as the stream time stamp.

VOB_A_GAP_LEN (VOB audio gap length)

Records the length of the audio reproduction gap
15 in 90 kHz precision.

CP_MNGI (copy management information) (Fig. 16)

Records the copy management information for the corresponding VOB, and comprises CPG_STATUS and CPGL.

20 CPG_STATUS (copy protection status)

Stores a value used for VOB copy protection. CPG_STATUS indicates whether content can be freely copied or whether only a first generation copy can be made.

CPGL (copy protection information)

25 Records the copy protection information applied

to the corresponding VOB.

TMAPI (time map information) (Fig. 18)

The time map information comprises TMAP_GI, TM_ENT, and VOBU_ENT fields.

5 TMAP_GI (Fig. 18)

The general TMAP information TMAP_GI comprises TM_ENT_Ns, VOBU_ENT_Ns, TM_OFS, and ADR_OFS fields as described below.

TM_ENT_Ns (TM_ENT number)

10 Records the number of TM_ENT fields in the TMAPI block as described below.

VOBU_ENT_Ns (VOBU_ENT number)

Records the number of VOBU_ENT fields in the TMAPI block as described below.

15 TM_OFS (time offset)

Records the time map offset with the video field precision.

ADR_OFS (address offset)

Records the offset in the first AV field in the VOB.

20 TM_ENT (time entry) (Fig. 18)

A time entry comprises the following fields as access point information at a constant time interval TMU. If the video format is NTSC, the TMU is 600 video fields; if PAL, it is 500 video fields.

25 VOBU_ENTN (VOBU_ENT number)

Records the entry number of a VOB containing the time $(TMU \times (N-1) + TM_OFS)$ for the N-th `TM_ENT` indicated by the `TM_ENT`.

5 `TM_DIFF` (time difference)

Records the difference between the time indicated by this `TM_ENT` and the presentation start time of the VOB pointed to by `VOBU_ENTN`.

`VOBU_ADR` (VOB address)

10 Records the start address in the VOB of the VOB pointed to by `VOBU_ENTN`.

`VOBU_ENT` (Fig. 19)

The VOB entry (`VOBU_ENT`) has the fields shown below for the corresponding VOB. The fields are formatted as shown in Fig. 19. The time and address information required to access a desired VOB can be obtained by simply adding the following fields in sequence.

`1STREF_SZ`

20 Stores the number of packs from the first pack in the VOB to the pack containing the last data block of the first I-picture in the VOB.

`VOBU_PB_TM`

Records the playback time of this VOB.

`VOBU_SZ`

25 Records the data size of this VOB.

S_AVFIT (Fig. 20)

The still image AV file information table comprises the following management information fields for

5 the still image AV file RTR_STO.VRO: S_AVFITI, S_VOB_STI, S_AVFI.

S_AVFITI (still image AV file information table information) (Fig. 20)

10 Stores the following information required to access S_VOB_STI and S_AVFI.

S_AVFI_Ns (still image AV file information number)

This is a value of either 0 or 1. This value corresponds to the number of still image AV files, that is, RTR_STO.VRO file presence.

15 S_VOB_STI_Ns (still image VOB stream information number)

Records the number of S_VOB_STI described below.

20 S_AVFI_EA (still image AV file information end address)

Records the S_AVFI end address.

S_VOB_STI (still image VOB stream information) (Fig. 20)

25 Records the following still image VOB stream information.

V_ATR (video attributes)

Information recorded as the video attributes are the Video compression mode, TV system, Aspect ratio, and Video resolution. These fields are as described above with reference to the video attributes V_ATR of the M_VOB_STI.

OA_ATR (audio stream attributes)

The audio stream attribute fields are: Audio coding mode, Application Flag, Quantization/DRC, fs, Number of Audio channels. These are also as described above with reference to the A_ATR0 fields of the M_VOB_STI.

SP_ATR (subpicture attributes)

The Application Flag is recorded for the subpicture attributes. This field is the same as SP_ATR described above with reference to M_VOB_STI.

SP_PLT (subpicture color palette)

Stores the color palette information for subpictures. The format is as described with reference to the SP_PLT of M_VOB_STI.

S_AVFI (still image AV file information) (Fig. 23)

Comprises the following fields required to access a still image VOG: S_AVFI_GI, S_VOGI_SRP, and S_VOGI.

S_AVFI_GI (Fig. 23)

General still image AV file information S_AVFI_GI

records S_VOGL_SRP_Ns.

S_VOGL_SRP_Ns (still image VOB group search
pointer number)

Records the number of S_VOGL_SRP fields
5 described below.

S_VOGL_SRP (still image VOB group information
search pointer) (Fig. 23)

Records S_VOGL_SA.

S_VOGL_SA (still image VOB group information start
10 address) records the start address of this S_VOGL.

S_VOGL (Fig. 23)

The still image VOB group information S_VOGL
comprises the following still image VOB management
15 information fields: S_VOG_GI, S_VOB_ENT, CP_MNGI.

S_VOG_GI (Fig. 23)

General still image VOB group information
S_VOG_GI records the following fields as general
information relating to the still image VOB group.

20 S_VOB_Ns (still image VOB number)

Records the number of still image VOBs in the
still image VOB group.

S_VOB_STIN (S_VOB_STI number)

Records the S_VOB_STI number storing the still
25 image VOB stream information. This S_VOB_STI number is

the recording sequence in the S_VOB_STI table.

FIRST_VOB_REC_TM (first VOB recording date/time)

Records the recording date/time information of the first still image VOB in the still image VOB group.

5 LAST_VOB_REC_TM (last VOB recording date/time)

Records the recording date/time information of the last still image VOB in the still image VOB group.

S_VOB_SA (still image VOB group start address)

10 Records the start address of the still image VOB group in the RTR_STO.VRO file.

CP_MNGI (copy management information)

Records copy management information relating to the corresponding still image VOB group. The fields thereof are the same as the above-described CP_MNGI for movie VOB information M_VOBI.

15 S_VOB_ENT (Fig. 24)

Still image VOB entries S_VOB_ENT are defined as either type A or type B as described below according to whether there is audio recorded for individual still image VOBs in the still image VOB group.

S_VOB_ENT (Type A) (Fig. 24)

Type A comprises the fields S_VOB_ENT_TY and V_PART_SZ, defined as follows.

S_VOB_ENT_TY (still image VOB entry type)

25 Still image VOB type information is formatted as

shown in Fig. 25.

MAP_TY

Stores one of the following values for identifying type A or type B.

5 00b: type A

01b: type B

TE

Stores one of the following values indicating the status of the still image VOB.

10 0b: normal

1b: temporarily or partially deleted

SPST_Ns

Stores the number of subpicture streams in the still image VOB.

15 V_PART_SZ (video part size)

Stores the data size of the video part of the still image VOB.

S_VOB_ENT (Type B) (Fig. 24)

In addition to S_VOB_ENT_TY and V_PART_SZ fields, type B also has A_PART_SZ and A_PB_TM fields as defined below.

20 S_VOB_ENT_TY (still image VOB entry type)

Records the type of the still image VOB. These fields are as described above with reference to type A.

25 V_PART_SZ (video part size)

Stores the data size of the video part of the still image VOB.

A_PART_SZ (audio part size)

Stores the data size of the audio part of the still image VOB.

A_PB_TM (audio playback time)

Stores the playback time (length) of the audio part of the still image VOB.

UD_PGCIT (Fig. 26)

The user-defined PGC information table comprises the following fields: UD_PGCITI, UD_PGCI_SRP, and UD_PGCI.

UD_PGCITI (Fig. 26)

The user-defined PGC information table information UD_PGCITI records the following fields constituting the user-defined PGC information table.

UD_PGCI_SRP_Ns (user-defined PGC information search pointer number)

Records the number of UD_PGCI_SRP fields.

UD_PGCIT_EA (user-defined PGC information table end address)

Records the UD_PGCIT end address.

UD_PGCI_SRP (Fig. 26)

The user-defined PGC information search pointer UD_PGCI_SRP records the UD_PGCI_SA field.

UD_PGCI_SA (user-defined PGC information start address)

Records the UD_PGCI start address. This address is used to seek and access the PGCI.

5 UD_PGCI (Fig. 26)

The detailed structure of the user-defined PGC information is described further below under the PGC information PGCI.

ORG_PGCI (Fig. 5)

10 The detailed structure of the original PGC information is described further below under the PGC information PGCI.

TXTDT_MG (Fig. 27)

15 The text data management field TXTDT_MG comprises TXTDTI, IT_TXT_SRP, and IT_TXT fields as described below.

TXTDTI (Fig. 27)

20 Text data information TXTDTI comprises the following fields: CHRS, IT_TXT_SRP_Ns, TXTDT_MG_EA.

CHRS (character set code)

Records the character set code used for IT_TXT.

IT_TXT_SRP_Ns (IT_TXT search pointer number)

Records the number of IT_TXT_SRP fields.

25 TXTDT_MG_EA (text data management end address)

Records the end address of the TXTDT_MG block.

IT_TXT_SRP (Fig. 27)

The IT_TXT search pointer IT_TXT_SRP records the following information for accessing IT_TXT.

5 IT_TXT_SA (IT_TXT start address)

Records the IT_TXT start address. This address is used to seek and access the IT_TXT block.

IT_TXT_SZ (IT_TXT size)

10 Records the IT_TXT data size. A desired IT_TXT block can be read by reading this amount of data.

IT_TXT (Fig. 27)

IT_TXT comprises one or more sets of three fields: identification code IDCD, the text TXT corresponding to that ID code, and an end code TMCD defining the end of the set. If there is no TXT field for an IDCD, the TXT field
15 can be omitted and IDCD and TMCD recorded as one set. Valid IDCD values are defined as follow.

Genre codes

30h: movie

20 31h: music

32h: drama

33h: animation

34h: sports

35h: documentary

25 36h: news

37h: weather

38h: educational

39h: hobby

3Ah: entertainment

5 3Bh: performing arts (plays, opera)

3Ch: shopping

Input source codes

60h: broadcasting station

61h: camcorder

10 62h: photograph

63h: memo

64h: other

PGCI (Fig. 28)

15 Original program chain information ORG_PGCI
and user-defined program chain information UD_PGCI have
a common data structure collectively referred to as program
chain information PGCI. PGCI comprises the following
fields: PGC_GI (program chain general information), PGI
20 (program information), CI_SRP (cell information search
pointer), and CI (cell information).

PGC_GI (Fig. 28)

PGC_GI (PGC general information) comprises the
fields PG_Ns (program number) and CI_SRP_Ns (cell
25 information search pointer number) as general information

about the PGC. These fields are described further below.

PG_Ns (program number)

Records the number of programs in the PGC. If a user-defined PGC, this field is 0 because there is no program.

CI_SRP_Ns (CI_SRP number)

Records the number of cell information search pointers CI_SRP, described below.

PGI (Fig. 28)

PGI (program information) comprises the following fields as described below: program type PG_TY, cell number C_Ns, primary text information PRM_TXTI, IT_TXT_SRPN, and THM_PTRI.

PG_TY (program type)

Records the following information formatted as shown in Fig. 29.

Protect (protected)

0b: normal

1b: protected

C_Ns (cell number)

Records the cell number in the program.

PRM_TXTI (primary text information)

Records the text information describing program content. For further details, see the above-noted PL_SRPT.

IT_TXT_SRPN (IT_TXT_SRP number)

If IT_TXT containing program content information is recorded in addition to the primary text noted above, the IT_TXT_SRP number recorded in TXTDT_MG is stored to this field.

5 THM_PTRI (thumbnail image pointer information)

Records the thumbnail image information representing this program. Details about the THM_PTRI are identical to the above-noted THM_PTRI of PL_SRPT.

CI_SRP (Fig. 28)

10 The cell information search pointer (CI_SRP) records address information required for accessing this cell information.

CI_SA (cell information start address)

Records the start address of the cell information.

15 The cell is accessed by seeking this address.

CI (Fig. 30)

CI (cell information) is one of two types: M_CI for movies, or S_CI for still image.

M_CI (Fig. 30)

20 M_CI (movie cell information) comprises the following fields: M_C_GI and M_C_EPI.

M_C_GI (Fig. 30)

M_C_GI (movie cell general information) contains the following basic information for each cell.

25 C_TY (cell type)

Records the following information formatted as shown in Fig. 31 for identifying movie cells and still image cells.

C_TY1

5 000b: movie cell

001b: still image cell

M_VOBI_SRPN (movie VOB information search pointer number)

10 Records the search pointer number of the movie VOB information corresponding to this cell. To access the stream data corresponding to this cell, it is first necessary to access the movie VOB information search pointer number indicated by this field.

C_EPI_Ns (cell entry point information number)

15 Records the number of entry points in this cell.

C_V_S_PTM (cell video start time)

Records the playback start time of the cell using the format shown in Fig. 10.

C_V_E_PTM (cell video end time)

20 Records the playback end time of the cell using the format shown in Fig. 10. Used in conjunction with C_V_S_PTM to define the valid cell period within the corresponding VOB.

M_C_EPI (Fig. 32)

25 M_C_EPI (movie cell entry point information) is

categorized as Type A or Type B based on the presence of primary text.

M_C_EPI (Type A) (Fig. 32)

M_C_EPI (Type A) contains the following
5 information indicative of an entry point.

EP_TY (entry point type)

Records the following information formatted as shown in Fig. 33 for identifying the entry point type.

EP_TY1

10 00b: Type A

01b: Type B

EP_PTM (entry point time)

Records the time at which the entry point is set according to the format as shown in Fig. 10.

15 M_C_EPI (Type B) (Fig. 32)

In addition to the same EP_TY and EP_PTM fields of Type A, M_C_EPI (Type B) has a PRM_TXTI field as described below.

PRM_TXTI (primary text information)

20 Records text information describing the content of the location indicated by the entry point. Details of this information are as described in the above-noted PL_SRPT.

S_CI (Fig. 30)

S_CI (still image cell information) comprises
25 S_C_GI and S_C_EPI fields.

S_C_GI (Fig. 30)

S_C_GI (still image cell general information)
contains the basic cell information described below.

C_TY (cell type)

- 5 Records information for identifying movie cells
and still image cells. This cell type information is as
described above with reference to a movie cell.

S_VOI_SRPN (still image VOB group information
search pointer number)

- 10 Records the search pointer number of the still
image VOB group information for the cell. To access the
stream data corresponding to the cell, it is first necessary
to access the still image VOB group information search
pointer number indicated by this field.

- 15 C_EPI_Ns (cell entry point information number)

 Records the number of entry points in this cell.

S_S_VOB_ENTN (starting still image VOB number)

- Records the still image VOB number from which
cell reproduction starts according to the format as shown in
20 Fig. 11. The still image VOB number is the sequence
number in the S_VOG pointed to by the above-noted
S_VOI_SRPN.

E_S_VOB_ENTN (end still image VOB number)

- Records the still image VOB number at which cell
25 reproduction ends according to the format as shown in Fig.

11. The still image VOB number is the sequence number in the S_VOG pointed to by the above-noted S_VOGL_SRPN. It should be noted that the valid cell period in the S_VOG to which the cell belongs is defined by this field in conjunction with S_S_VOB_ENTN.

S_C_EPI (Fig. 32)

S_C_EPI (still image cell entry point information) is categorized as Type A or Type B depending upon the presence of primary text.

10 S_C_EPI (Type A) (Fig. 32)

S_C_EPI (Type A) contains the following information indicative of an entry point.

EP_TY (entry point type)

Records the following information formatted as shown in Fig. 33 for identifying the entry point type.

EP_TY1

00b: Type A

01b: Type B

S_VOB_ENTN (still image VOB entry number)

20 Records the still image number in which the entry point is set according to the format as shown in Fig. 11.

S_C_EPI (Type B) (Fig. 32)

In addition to the same EP_TY and S_VOB_ENTN fields of Type A, S_C_EPI (Type B) has a PRM_TXTI as described below.

PRM_TXTI (primary text information)

Records text information describing the content of the location indicated by the entry point. Details of this information are as described in the above-noted PL_SRPT.

5

Configuration of a DVD recorder

The configuration of a DVD recorder is described next below with reference to Fig. 40.

As shown in the figure, this DVD recorder
10 comprises a user interface 7801 for interaction with the user; a system controller 7802 for handling overall management and control of the recorder; an input block 7803 comprising an A/D converter for audio and video input to the recorder; an encoder 7804; an output section 7805
15 for audio and video output; a decoder 7806 for MPEG stream decoding; track buffer 7807; and drive 7808.

Operation of a DVD recorder

The basic recording and reproduction operation
20 of a DVD recorder shown in Fig. 40 is described next below.

A recording operation is described first below.

Before recording starts, the input block 7803, encoder 7804, and track buffer 7807 are initialized by a command from the system controller 7802. Audio and video
25 data input to the input block 7803 are A/D converted and

passed to the encoder 7804. The encoder 7804 compresses and multiplexes the video and audio data to generate a MPEG system stream, which it then passes to the track buffer 7807. Data is then passed sequentially from the track
5 buffer 7807 to the drive for recorded to DVD-RAM disc.

A reproduction operation is described next.

After inserting a DVD-RAM disc to the disc player for reproduction, the user selects the AV stream to be played from among the plural AV streams on the disc. The
10 method whereby the user selects the desired AV stream is described in particular detail below.

As noted above, a plurality of AV streams can be recorded to a single disc. It is therefore essential that the disc player be able to present to the user a list of all AV
15 streams currently on the disc.

As also described above each AV stream is managed using video object VOB units. Video object information VOB I is recorded specifically for each VOB to record and manage attribute information for each VOB. A
20 sequence of one or a plurality of VOBs is managed using a program chain PG defining a hierarchical sequence of VOBs. This program concept is introduced so that bitstreams representing a linear stream of data can be managed when recorded for whatever reason as a plurality of AV streams.
25 This program concept is useful for managing separately

recorded scenes as a meaningful sequence of related events. For example, an AV stream of a tug-of-war recorded during morning using a disc camera, and another AV stream of a relay race recorded in the afternoon could be linked and managed as a single program titled as a "school field day." Program information PGI is recorded for each program. The title associated with a particular program is recorded and managed within the attribute information for that program.

10 The program is thus a useful unit for recording and reproducing AV content in a way that can be easily understood by and presented to the user, while the video object VOB is the unit whereby these AV streams are internally managed by the DVD recorder.

15 Management information as related to the present invention and applied to actual AV stream data is described next below with reference to Fig. 46.

 Row L1 in Fig. 46 shows program chain information PGCI. The left block L1a shows the original program chain information ORG_PGCI required to reproduce an AV stream as it was recorded. The right block L1b and L1c show the user-defined program chain information UD_PGCI required to reproduce a program chain as edited and defined by the user.

25 The hierarchical structure of the ORG_PGCI

management information is shown in Fig. 5, Fig. 28, and Fig. 30. The hierarchical structure of the UD_PGCI management information is shown in Fig. 5, Fig. 26, Fig. 28, and Fig. 30.

5 It should be noted that plural UD_PGCI can be recorded to a single disc. The UD_PGCIT (user defined program chain information table) as shown in Fig. 5 is therefore used as a table of these UD_PGCI from which a user can select a particular UD_PGCI for reproduction.

10 The title of the first recorded program can be obtained by tracing a path through the management information in the order described below with reference to Fig. 46.

S1 in Fig. 5 → S2 → S3 in Fig. 28.

15 The second row L2 in Fig. 46 shows the still image VOB management information S_VOBI and movie VOB management information M_VOBI. Up to 999 M_VOBI management information blocks can be recorded to an optical disc. The hierarchical structure of this M_VOBI management information is shown in Fig. 5, Fig. 15, and
20 Fig. 16.

 Whether a cell in the program chain information PGCI in row L1 is associated with any movie VOB management information M_VOBI in row L2 can be known
25 from the management information described below.

S1 in Fig. 5 → S2 → S3 in Fig. 28 (C_Ns is the number of cells in the program. By counting the number of cells contained in a program in sequence from the first program, the number of a cell contained in the desired
5 program is obtained. The number of the obtained cell is used as the cell search pointer CI_SRP#n.)

→ S5 → S6 → S7 (Obtain the cell address based on the cell search pointer.)

10 → S8 (Obtain the number of the address cell information.)

→ Fig. 30, S9 (movie cell information M_CI)

→ S10 (movie cell general information M_CGI.)

→ S11 (movie VOB information search pointer number M_VOBI_SRPN)

15 → Fig. 5, S12 (AV file information table)

→ Fig. 15, S13 → S14 → S15 (access the movie VOB information search pointer detected in S11)

→ S16 → S17 (determine the movie VOB information start address)

20 → S18 → S19

Row L3 in Fig. 46 shows the movie VOB stream information M_VOB_STI. Application Flag and Preference Flag according to the present invention are written to M_VOB_STI. That is, as shown in Fig. 12, M_VOB_STI
25 contains audio attributes A_ATTR0 and A_ATTR1. As shown in

Fig. 13, audio attributes A_ATR0 and A_ATR1 contain an Application Flag (b17, b16) and Preference Flag (b19, b18).

A maximum 64 M_VOB_STI can be written to one optical disc. One M_VOB_STI is allocated to each one M_VOBI, and M_VOB_STI of identical content are often allocated to plural M_VOBI. In this case a common M_VOB_STI can be linked to multiple M_VOBI. For example, M_VOBI#1 and M_VOBI#2 are linked to a common M_VOB_STI#2 in Fig. 46.

The link between a particular M_VOBI and any particular M_VOB_STI can be known from management information as described next below.

In the above sequence of steps it was determined in step S19, Fig. 5, what movie VOB management information M_VOBI is linked to what cells in the program chain information PGCI in Fig. 46. The M_VOB_STI linked to movie VOB management information M_VOBI is obtained as follows.

Fig. 5, S19 → S20 → Fig. 16, S21 (M_VOB_STIN indicates a stream information number of the movie VOB).

The Application Flag (b17, b16) and Preference Flag are obtained from this M_VOB_STIN as follows.

Fig. 5, S12 → Fig. 12, S22 → S23 → S24

Fig. 47 is a flow chart of a process whereby a DVD-RAM disc is recorded by a DVD recorder according to the present invention. The steps in this process are

described below.

Step #1: The disc recorder/player shown in Fig. 40 is initialized. N_AC1 memory, N_AC2 memory, AP_FLG1 memory, AP_FLG2 memory, and PR_FLG memory in the system controller 7802 are initialized. N_AC1 and N_AC2 are for temporarily recording the number of audio channels in audio stream 1 and audio stream 2. PR_FLG stores the user's channel preference. For example, if dual monaural recordings in Japanese and English are present, and the user prefers to listen in English, the Preference Flag information indicating that audio channel 2 should be preferentially reproduced is stored temporarily to memory. AP_FLG1 and AP_FLG2 store the audio stream 1 and audio stream 2 application information, that is, whether a mixed combination of plural audio channels is recorded. Information indicative of, for example, whether monaural, stereo, and dual monaural audio recordings are mixed in the single AV stream selected by the particular M_VOB_STI is temporarily stored in memory. A typical mixed audio application as shown in Fig. 42 (c) might be a movie broadcast in Japanese and English using dual monaural channels and commercials recorded in stereo.

In Step #1 in this example, memory N_AC1 and N_AC2 are initialized to 1111b, and AP_FLG1 and AP_FLG2 are initialized to 00b, where "b" indicates binary code.

PR_FLG is set to the preset value selected by the user by means of user interface 7801, or to the default value if no user preference has been defined.

Step #2: The input block 7803 sends the A/D converted input signal data (note that while both audio and video data is received and converted, we focus herein on the audio data) and the audio channel information extracted from the input signal to the encoder 7804.

Step #3: The encoder 7804 encodes the audio data according to the audio data configuration, sends the encoded audio data and video data, that is, the encoded AV stream data, to the track buffer, and sends the audio channel information to the system controller 7802.

Step #4: The system controller 7802 converts the received audio channel information for audio stream 1 or audio stream 2 to the above-noted 4-bit ID code, and buffers this data to N_AC1 or N_AC2. For example, if the ID code is 0001b, the audio channel information is known to be two channel (stereo).

Step #5: If the audio channel for audio stream 1 or audio stream 2 differs within the same AV stream from the audio channel information previously received by the system controller 7802, AP_FLG1 or AP_FLG2 is set to 01b. For example, if different audio channel configurations are mixed within a single audio stream as shown in Fig. 42 (c),

the Application Flag is set to 01b as noted above, indicating that the audio stream contains a mixed audio channel configuration.

Step #6: The system controller 7802 controls the drive to sequentially read the AV stream data from the track buffer 7807 and record it to disc.

Step #7: Whether there is more data to be input to the same AV stream is then detected. If there is, the procedure loops back to step #2 and repeats. If not, it advances to step #8. In other words, step #8 begins when recording one AV stream is completed.

Step #8: Recording the movie VOB management information M_VOBI for the AV stream (VOB) that has been completely recorded begins to the RTR.FO file. It should be noted that most of this management information is temporarily stored in memory by the system controller 7802.

Step #9: Information in N_AC1 memory about the number of audio channels stored, and information in AP_FLG1 memory indicative of whether a mixed audio channel configuration is recorded, is recorded to ATR0 in stream information M_VOB_STI, that is, to areas b11, b10, b9, and b8, and b7 and b16 in the A_ATR0 format shown on the bottom in Fig. 13. Data from memory N_AC2 and AP_FLG2 is likewise recorded in ATR1 of stream information M_VOB_STI.

Step #10: User preference information recorded to PR_FLG memory is recorded to ATR0 in stream information M_VOB_STI, that is, to areas b19, b18 in the A_ATR0 format shown on the bottom in Fig. 13. Other
5 information is also recorded to complete M_VOB_STI, and recorded to the RTR.IFO file.

Step #11: Cell information CI corresponding to the recorded VOB and program information PGI are generated and appended to the end of the original program
10 chain information ORG_PGCI.

As shown in Fig. 50, when a DVD-RAM disc according to the present invention is loaded into a disc player, a list of all programs (for example, television dramas, sitcoms, documentaries, new movies, other)
15 recorded to the DVD-RAM disc is presented by means of the output section 7805 for the user to review. The configuration of the audio accompanying each program is also indicated in this program list.

Fig. 48 is a flow chart of a process for presenting
20 a program list, and particularly information relating to the audio content configuration, for the user. The example described below addresses presenting a program list for an original program, that is, program content not edited by the user. The steps in this process follow.

25 Step #20: A counter N for counting the number of

programs is reset to zero.

Step #21: Counter N is incremented 1.

Step #22: Program information PGI for the N-th program is read.

5 Step #23: The title is read from the PRM_TXTI field of the PGI.

Step #24: The cell information CI for the PGI is read to obtain the movie VOB information search pointer number M_VOBI_SRPN.

10 Step #25: Using M_VOBI_SRPN, the corresponding movie VOB management information M_VOBI is read and the movie VOB stream information number M_VOB_STIN is detected.

Step #26: Using M_VOB_STIN, A_ATR0 in the
15 movie VOB stream information M_VOB_STI of the corresponding M_VOB is read, and the Application Flag, Preference Flag, and audio channel count for audio stream 1 are detected. A_ATR1 is likewise read, and management information is found therein the Application Flag,
20 Preference Flag, and audio channel count for audio stream 2 are also detected.

Step #27: Whether there is a next program information PGI is determined. If there is, the procedure loops back to step #21; if not, the procedure advances to
25 step #28.

Step #28: Using the title detected in step #23 and the Application Flag, Preference Flag, and audio channel count detected in step #26, a program list screen is generated and presented. This program list also displays
5 based on the information from A_ATR0 whether for audio stream 1 there is a mixed configuration of plural audio channels, whether an enhancement channel is present, and the number of audio channels. Based on the information from A_ATR1, it is also indicated for audio stream 2
10 whether there is a mixed configuration of plural audio channels, whether an enhancement channel is present, and the number of audio channels. If both A_ATR0 and A_ATR1 are present, the program list indicates that there are two audio streams available; if only A_ATR0 information is
15 present, the program list indicates there is only one audio stream available.

Step #29: Referring to the displayed program list, the user selects a program by way of user interface 7801.

Step #30: The disc player then plays the selected
20 program. The process for this is shown in the flow chart of 49 and described below.

A typical program list display is described below with reference to Fig. 50.

The numbers 1, 2, 3 on the left side of the
25 display are sequential program numbers. The titles are

shown in the middle column. In this example the program list includes a television drama, overseas documentary, and a new movie. This information is stored to the PRM_TXTI field of the program information PGI of the original program chain information ORG_PGCI written to the optical disc.

The third column (including two audio streams, monaural, and stereo, for example) shows the audio stream configuration of the corresponding program. This information relates to the audio stream contained in the VOB referenced from a cell contained in the corresponding program, and is generated and displayed using the ATR0 or ATR1 information recorded to the M_VOB_STI specified by M_VOB_STIN in the VOB. The user knows from this information the configuration of the audio stream contained in the program, and can thus determine what audio streams can be selected and the typical format of an audio stream when reproduced.

For example, it can be determined before playback begins that if the user selects the "overseas documentary", audio stream 1 of the dual monaural audio content will be reproduced based on the information recorded to ATR0, and that in accordance with the Preference Flag of ATR0 storing the user's preference, audio channel 1 (main audio) will be reproduced by default.

Likewise, if the "new movie" is selected, it can be

known from the information recorded to the Number Of Audio Channels and the Application Flag recorded to ATR0 that audio stream 1 contains a mixture of dual monaural and other audio content, and that the user's preference
5 specified by the Preference Flag is to listen to audio channel 2 (sub) in the representative dual monaural parts of the audio content.

It will thus be obvious that information from ATR0 and ATR1 can be presented to the user when allowing the
10 user to select the program to be reproduced. The user can thus know basic information about the various possible audio stream configurations, such as how many audio streams are available, the channel configuration of each audio stream, and whether the channel configuration
15 includes multiple modes mixed together, before a selection is made and playback starts, thus avoiding confusing the user when playback actually begins.

It is also possible to set for each VOB whether to select audio channel 1 or 2 when the audio stream is a dual
20 monaural configuration, and the user can record using the Preference Flag of ATR0 and ATR1 which audio channel is preferred.

Moreover, if the disc player has a function for automatically selecting and reproducing the audio channel
25 specified by the Preference Flag of a particular VOB, the

user can preprogram the disc player once with the user's preferred audio channel selection so that the desired audio channel will always be automatically selected and played without the user needing to change the audio channel at all.

5

The playback operation performed after the user selects the program to be reproduced is described next below.

The track buffer 7807, decoder 7806, and output
10 section 7805 are initialized by a command from the system controller 7802. The system controller 7802 then instructs the disc drive to seek the start address of the AV data in the first VOB of the selected program. The drive then begins reading the data and passes the read AV data to the
15 track buffer 7807. The decoder 7806 reads data from the track buffer 7807, extracts the decompressed AV data by applying an MPEG decoding operation, and passes the decompressed AV data to the output section 7805. The output section 7805 D/A converts the data and outputs the
20 resulting analog AV data to the television or other AV device connected to the output terminal.

Fig. 49 is a flow chart of a playback process for reproducing a program selected from the presented program list. The steps in this process are described next below.

25

Step #40: The cell information CI for the program

information PGI of the selected program is read to obtain
M_VOB_SRPN.

Step #41: The corresponding M_VOBI is read
from the detected M_VOB_SRPN to obtain the VOB data
5 read address.

Step #42: M_VOB_STIN is obtained from M_VOBI.

Step #43: Using M_VOB_STIN, the decoder is set
to the attributes of the corresponding VOB stream. It should
be noted that the audio stream attributes used to setup
10 decoder operation at this time are the audio stream
attributes related to the present invention, such as
information about the number of audio channels and
whether there is a mixed configuration of multiple audio
channels.

15 Step #44: If there are two audio streams, one is
selected by means of the user interface of the disc player.
If there are multiple audio channels in the selected audio
stream, or in the audio stream itself if there is only one
audio stream from the start, and user preference
20 information is also recorded, the audio channel indicated by
the user preference information is selected. If preference
information is not recorded, a default audio channel, such
as audio channel 1, is selected.

25 Step #45: The decoder is set to the selected
audio channel.

Step #46: VOB data is read from the read address, buffered to the track buffer, and supplied to the decoder.

Step #47: The decoder decodes the audio
5 channel selected in step #44.

Step #48: Whether there is further VOB data to be read is determined. If there is, the procedure loops back to step #40; if not, the process ends.

It should be noted that the preferred embodiment
10 of the invention is described above with reference to a DVD-RAM disc, but it will be obvious to one with ordinary skill in the related art that any rewritable optical disc can be alternatively used. Also, the invention is not restricted to optical disc, but can be applied to a hard disk or even
15 distributable flash memory, i.e., a rewritable, random accessible storage medium of sufficient capacity.

In addition, preference information regarding two audio channels of a dual monaural configuration are used as the Preference Flag values stored to ATR0/ATR1 above,
20 but preference information defining a preferred selection from among plural audio streams can be alternatively used.

Yet further, the Application Flag information stored to ATR0/ATR1 as described above indicates whether a mixed configuration of plural audio channels is recorded,
25 or whether an audio enhancement channel for the visually

impaired is recorded. Other possible Application Flag values include information indicating whether audio in a particular language is recorded. The DVD recorder as referred to above is also assumed to have both recording and playback capabilities in a single unit, but the benefits of the present invention can also be achieved using a dedicated disc recorder and a separate dedicated disc player.

By recording information indicating the type of an audio stream configuration contained in AV data recorded to optical disc, meaningful information enabling the user to select a desired AV stream for reproduction can be presented to the user, thereby avoiding user confusion and making the optical disc and disc player easier to operate and use.

Furthermore, by recording user preference information, it is additionally possible to provide a disc player capable of automatically selecting and reproducing an appropriate audio channel conforming to the user preference.

Although the present invention has been described in connection with the preferred embodiments thereof with reference to the accompanying drawings, it is to be noted that various changes and modifications will be apparent to those skilled in the art. Such changes and

modifications are to be understood as included within the scope of the present invention as defined by the appended claims, unless they depart therefrom.

CLAIMS

1. An optical disc for storing an AV stream containing a video stream and at least one audio stream,
5 and management information for managing the AV stream, wherein:

the audio stream comprises an audio channel area containing first audio channel data and second audio channel data, one of which is selectively reproduced; and

10 the management information comprises preference information indicative of whether the first audio channel data or second audio channel data is preferentially reproduced when the audio channel area is reproduced.

15 2. An optical disc for storing an AV stream containing a video stream and at least one audio stream, and management information for managing the AV stream, wherein:

20 the audio stream contains at least two of the following areas,

a first area containing first audio channel data and second audio channel data, one of which is selectively reproduced,

25 a second area containing simultaneously reproduced first audio channel data and second audio

channel data, and

a third area containing data for one audio channel; and

the management information contains application
5 information indicative that two or more different audio stream areas are contained in one audio stream.

3. A recording device for recording to an optical disc an AV stream containing a video stream and at least
10 one audio stream, and management information for managing the AV stream, comprising:

an encoder (7804) for encoding an audio stream having an area containing first audio channel data and second audio channel data, one of which is selectively
15 reproduced;

a controller (7802) for generating management information containing preference information indicative of whether the first audio channel data or second audio channel data is preferentially reproduced when the audio
20 channel area is reproduced; and

drive means (7807, 7808) for recording the encoded audio stream and management information to a data area of the optical disc.

25 4. A recording device as described in claim 3,

wherein:

the encoder further encodes an audio stream containing at least two of the following areas,

a first area containing first audio channel data and second audio channel data, one of which is selectively reproduced,

a second area containing simultaneously reproduced first audio channel data and second audio channel data, and

a third area containing data for one audio channel; and

the controller generates management information containing application information indicative that two or more different audio stream areas are contained in one audio stream.

5. A playback device for reproducing an optical disc to which are recorded an AV stream containing a video stream and at least one audio stream, and management information for managing the AV stream, comprising:

reading means (7807, 7808) for reading management information from a data area of the optical disc;

extraction means (7802, Step #26) for extracting preference information contained in the management

information,

the preference information indicating whether the first audio channel data or second audio channel data is preferentially reproduced when reproducing the area containing first audio channel data or second audio channel data of which one is selectively reproduced; and

a decoder (7806) for selecting and decoding audio channel data indicated by the preference information.

10

6. A playback device as described in claim 5, further comprising an output means (7805) for displaying a preferred audio channel as determined by the preference information.


15


7. A playback device as described in claim 6, wherein the extraction means further extracts application information indicating two or more areas of different type are mixed in a single audio stream; and

20

the output means displays information indicating presence of a mixture of audio types.

Fig.1








Fig.4






Fig.5

Fig.6






Fig. 9

[illegible]

PL_CREATE_TM									
b39	b38	b37	b36	b35	b34	b33	b32		
Year[13..6]									
b31	b30	b29	b28	b27	b26	b25	b24		
Year[5..0]				Month[3..2]					
b23	b22	b21	b20	b19	b18	b17	b16		
Month[1..0]		Day[4..0]				Hour[4]			
b15	b14	b13	b12	b11	b10	b9	b8		
Hour[3..0]			Minute[5..2]						
b7	b6	b5	b4	b3	b2	b1	b0		
Minute[1..0]		Second[5..0]							

Fig.12




Fig. 15




Fig.16





Fig.18






Fig. 21

[illegible]

OA_ATR									
b15	b14	b13	b12	b11	b10	b9	b8		
Audio coding mode						reserved			
b7	b6	b5	b4	b3	b2	b1	b0	Application Flag	
Quan./DRC			fs	Number of Audio channels					

Fig.23




Fig.24

S_VOB ENT (TYPE A)	2bytes
S_VOB ENT_TY	1byte
V_PART_SZ	1byte

S_VOB ENT (TYPE B)	6bytes
S_VOB ENT_TY	1byte
V_PART_SZ	1byte
A_PART_SZ	2bytes
A_PB_TM	2bytes

Fig.26




Fig.27




Fig.28




Fig.30




Fig.31

C_TY										
b7	b6	b5	b4	b3	b2	b1	b0			
C_TY1		reserved								

Fig.32

M_C_EPI (Type A)		7bytes
EP_TY		1byte
EP_PTM		6bytes


S_C_EPI (Type A)		7bytes
EP_TY		1byte
S_VOB_ENTN		6bytes

M_C_EPI (Type B)		135bytes
EP_TY		1byte
EP_PTM		6bytes
PRM_TXTI		128bytes

S_C_EPI (Type B)		135bytes
EP_TY		1byte
S_VOB_ENTN		1byte
PRM_TXTI		128bytes

Fig. 33

[illegible]








Fig.35(b) DATA ACCUMULATED IN THE TRACK BUFFER



36/50






Fig.37

38/50




Fig. 39(a) VIDEO




Fig. 39(b) VIDEO BUFFER




Fig. 39(c) MPEG STREAM




Fig. 39(d) AUDIO






Fig.41




Fig.42(a) AV STREAM 1




Fig.42(b) AV STREAM 2




Fig.42(c) AV STREAM 3






Fig.43 AV STREAM 1



ATR0	Preference Flag=00b (INAPPLICABLE) Application Flag=00b (INAPPLICABLE) Number of Audio channels=0000b (MONAURAL)
------	--

ATR1	Preference Flag=00b (INAPPLICABLE) Application Flag=00b (INAPPLICABLE) Number of Audio channels=0000b (STEREO)
------	--

Fig.44 AV STREAM 2



ATR0 Preference Flag=01b (PREFER AUDIO CHANNEL 1)
 Application Flag=11b (SUB AUDIO IS CONTAINED)
 Number of Audio channels=1001b (DUAL MONAURAL)

ATR1 (NOT CONTAINED)

Fig.45 AV STREAM 3






Fig. 46




47/50

Fig.47



48/50

Fig.48



49/50

Fig.49




Fig. 50

PROGRAM LIST	
1 TV DRAMA	(2 AUDIO STREAMS, MONAURAL AND STEREO)
2 FOREIGN DOCUMENTARY	(1 AUDIO STREAM, DUAL MONAURAL PREFER MAIN AUDIO)
3 NEW MOVIE THEATER	(1 AUDIO STREAM, PLURAL AUDIO CHANNEL CONFIGURATION ARE MIXED, MAIN MODE IS DUAL MONAURAL, DUAL MONAURAL PREFERS SUB AUDIO)

NAMES INDICATE EACH PROGRAM
(DISPLAYED BY USING PRIMARY TEXT
INFORMATION OF EACH PGI IN DISK)

INFORMATION ABOUT AUDIO STREAM FOR AV STREAM INCLUDED IN
EACH PROGRAM (GENERATED AND DISPLAYED BY USING INFORMATION
OF PREFERENCE FLAG, APPLICATION FLAG AND NUMBER OF AUDIO
CHANNELS IN ATOR0 / ATR1)

INTERNATIONAL SEARCH REPORT

Int. J. Application No

PCT/JP 00/01995

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G11B27/32 H04N5/775 G11B27/10 G11B19/02 H04N5/92
H04N9/82 G11B27/34 //H04N5/85,G11B7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G11B H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97 46007 A (THOMSON CONSUMER ELECTRONICS) 4 December 1997 (1997-12-04) the whole document	1-3,5
A	EP 0 521 487 A (SONY CORP) 7 January 1993 (1993-01-07) the whole document	1-7
A	EP 0 896 335 A (MATSUSHITA ELECTRIC IND CO LTD) 10 February 1999 (1999-02-10) the whole document	1-7
A	WO 95 12180 A (TIME WARNER ENTERTAINM CO LP) 4 May 1995 (1995-05-04) page 24, line 25 -page 28, line 10	1-7
	—/ —	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

7 August 2000

Date of mailing of the international search report

16/08/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Daalmans, F

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 727 780 A (TOKYO SHIBAURA ELECTRIC CO) 21 August 1996 (1996-08-21) the whole document	1-3,5
A	US 5 751 371 A (SHINTANI PETER) 12 May 1998 (1998-05-12) the whole document	1-3,5

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9746007	A	04-12-1997	US 5838873 A	17-11-1998
			AU 3150797 A	05-01-1998
			AU 3150897 A	05-01-1998
			AU 3209497 A	05-01-1998
			AU 716349 B	24-02-2000
			AU 3213297 A	05-01-1998
			AU 3213397 A	05-01-1998
			BR 9709409 A	10-08-1999
			BR 9709410 A	10-08-1999
			BR 9709420 A	10-08-1999
			BR 9709494 A	10-08-1999
			BR 9709508 A	10-08-1999
			CN 1226354 A	18-08-1999
			CN 1226359 A	18-08-1999
			CN 1226355 A	18-08-1999
			CN 1226356 A	18-08-1999
			CN 1226357 A	18-08-1999
			EP 0903033 A	24-03-1999
			EP 0903034 A	24-03-1999
			EP 0903035 A	24-03-1999
			EP 0903036 A	24-03-1999
			EP 0903038 A	24-03-1999
			PL 330219 A	10-05-1999
			WO 9746008 A	04-12-1997
			WO 9746017 A	04-12-1997
			WO 9746009 A	04-12-1997
			WO 9746010 A	04-12-1997
			US 5844595 A	01-12-1998
			US 5844478 A	01-12-1998
			US 5754651 A	19-05-1998
			US 5933500 A	03-08-1999
EP 0521487	A	07-01-1993	JP 5012804 A	22-01-1993
			JP 5012831 A	22-01-1993
			DE 69222235 D	23-10-1997
			DE 69222235 T	15-01-1998
			US 5715224 A	03-02-1998
			US 5933398 A	03-08-1999
EP 0896335	A	10-02-1999	AU 8560598 A	01-03-1999
			AU 8560698 A	01-03-1999
			AU 8560898 A	01-03-1999
			EP 0896336 A	10-02-1999
			EP 0896337 A	10-02-1999
			WO 9908280 A	18-02-1999
			WO 9908281 A	18-02-1999
			WO 9908282 A	18-02-1999
			JP 11120747 A	30-04-1999
			JP 11120748 A	30-04-1999
WO 9512180	A	04-05-1995	JP 11120749 A	30-04-1999
			US 5469370 A	21-11-1995
			AT 194241 T	15-07-2000
			AU 673635 B	14-11-1996
			AU 7982394 A	22-05-1995
			CA 2175064 A,C	04-05-1995
			DE 69425069 D	03-08-2000
			EP 0729621 A	04-09-1996

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 00/01995

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9512180	A		EP 0967610 A	29-12-1999
			JP 2948911 B	13-09-1999
			JP 8510850 T	12-11-1996
EP 0727780	A	21-08-1996	DE 727780 T	13-02-1997
			JP 8287613 A	01-11-1996
			US 5915066 A	22-06-1999
US 5751371	A	12-05-1998	JP 8181929 A	12-07-1996